

C.K

SITE LIGHT 5000lm

IMPORTANT! RETAIN FOR FUTURE REFERENCE: READ CAREFULLY!

Technical specifications:

Protection class III
Protection degree IP54

Illuminant 45W,96* SMD

Luminous flux 5000lm(100%) 3750lm(75%) 2500lm(50%) 1250lm(25%)

Operating time Approx.

30min/1.5Ah at 100% 40min/1.5Ah at 75% 60min/1.5Ah at 50% 120min/1.5Ah at 25%

Battery Li-ion 18V Operating temperature -10°C - +40°C

Dimensions (L/B/H) $261.9 \times 201.7 \times 170.7$ mm

Net weight 1.32kg

Proper intended use:

The working light is only suitable for indoor lighting applications.

Press the on/off switch on the back.

Choose desired switch stage: 100% Power - 75% Power - 50% Power - 25% Power.

Low battery warning: The light will flash 4 - 6 times before battery runs out.

Safety Notes:

- I. Prior to each charge, make sure the light is not damaged in any way. Never use the lamp if you find damage.
- 2. Do not use the lamp in explosive environments in which flammable liquids, gases or dusts are present. Risk to life!
- 3. LED lights are extremely bright. Do not look directly at the lamp.

CAUTION RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS

Maintenance:

PLEASE NOTE:

The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.

Cleaning

Do not use solvents, corrosive cleaners or the like. Use a dry or slightly moist cloth for cleaning ONLY.

Disposal



Dispose of electrical devices in an environmentally responsible manner! Do not dispose of electrical devices with household rubbish.

In accordance with European Directive 2012/19/EU regarding electrical and electronic devices must be collected separately and sent in for recycling.

Please contact your local authorities for available disposal options for your worn-out device.

Address

Carl Kammerling International Limited,

C.K House, Glanydon Industrial Estate, PWLLHELI, LL53 5LH, United Kingdom www.carlkammerling.com